

Application

Widely used in internal residential and commercial applications. To accommodate different building designs, panels can slide to one or both sides.

Panel Specification

Track System:	Quick Run 120		
Hanger	57JNP	58JNP	61JNP
For Individual Panels:			
Max Panel Height	3000mm	3000mm	3000mm
Max Panel Weight	120kg	120kg	120kg
Min Panel Thickness	28mm	32mm	32mm

For ease of operation it is recommended that the panel width should not exceed 75% of panel height.

Timber panels for interior use can be of flush construction or glazed. Timber panels for industrial applications should be framed, ledged and braced. Metal panels should be constructed of box section, channel or angle framing, well braced and clad with flat or corrugated sheets.

Standard Sets and Packs

Sets comprise of top track, hangers, doors stops, nylon guides, timber screws and instructions.

Set No.	Max. Panel Width	Track Length	Hanger Details
QR120S-C20F/1	950mm	2000mm	57JNP Surface mount Hanger
QR120R-C20F/1	950mm	2000mm	58JNP Recessed mount Hanger
QR120Z-C20F/1	950mm	2000mm	61JNP Zero Clearance Hanger

*Standard Sets are available in kits for ceiling and flushed Tracks in 2000mm and 3000mm lengths with and without soft close / clip stop.

Pack Set No.	Description
QR120S-C1PK	Surfaced mounted hanger with clip stop, 1 panel pack, no track
QR120R-C1PK	Recessed mounted hanger with clip stop, 1 panel pack, no track
QR120Z-C1PK	Zero clearance hanger with clip stop, 1 panel pack, no track

Hardware Specification

Track:	120C, 120E, 120F
Material	Aluminium
Finish	Clear anodised
Standard lengths	2000mm, 3000mm, 4000mm and 6000mm

Brackets:	91
Face fitted stainless steel angle	5SS/120
Double face fitted bracket SS	
Fit at 400mm maximum centres	

Hangers (2 per panel):	
Timber panels - plate (surface)	57JNP
Timber panels - plate (recessed)	58JNP
Timber panels - Zero Clearance	61JNP

Hangers supplied with fixing plate and nylon tyred precision bearings. Vertical adjustment is simple and positive. Nylon tyre wheel hangers should not be used on installations involving temperatures exceeding 80°C.

Guides:	
Timber panels - SS plate (94 channels)	106E/94
Timber panels - SS plate	104W/94PR
Timber panels - nylon guide	101N
Multiple panels - bearing	106A/94
Multiple panels - T slot	106AT

Channels:	
Aluminium & Polypropylene	94PPA Mill or clear anodised
Aluminium	94A Mill or clear anodised
	96W Clear anodised
Brass	94B
Standard lengths	2000mm, 3000mm, 4000mm and 6000mm

Accessories:	
Door Collector - multiple panels	924-DC
Clip Stop	120CS
Soft Close	120SCT
Telescopic Accessory Kit - 2 door panel	TEL/2
Fascia & end caps in CA	123

Flush bolts and flush pulls are available in (PVDB) PVD Brass, (SN) Satin Nickel & (PN) Polished Nickel





